


QUALITY CONTROLS, INC. 200 Tilton Road





Phone: (603) 286-3321 Fax: (603) 286-7648 Web: <u>www.qcivalves.com</u>

Cv Ratings for 1/4" thru 4" Valves End Connections: 150# Flange, FNPT, Butt Weld, Socket Weld

	PORTING TYPE		
VALVE SIZE	2-WAY, "S"	3-WAY, "L" & "T" (ANGLE RUN)	3-WAY, "T" (STRAIGHT RUN)
1/4"	5.9	2.8	4.3
3/8"	5.9	2.8	4.3
1/2"	10.5	2.8	4.3
3/4"	26	9	18
1"	51	19	47
11/4"	51	19	47
1½"	129	45	98
2"	200	74	152
2½"	375	138	327
3"	466	195	405
4"	1441	375	968

	PORTING TYPE		
VALVE SIZE	4-WAY, "LL"	5-WAY, "B" (BOTTOM PORT, ANGLE RUN)	
1/4"	1.4	2.8	
3/8"	1.4	2.8	
1/2"	1.4	2.8	
3/4"	6.6	9	
1"	14.8	19	
11/4"	14.8	19	
1½"	35	45	
2"	41	74	
2½"	136	138	
3"	189	195	
4"	377	375	

Notes:

- 1. Cv is defined as the number of U.S. gallons of water per minute, 60 F at 14.7 PSIA, that will flow through a valve at a 1 PSIG pressure drop across the Valve.
- 2. The above Cv ratings are as tested by an independent test facility.