



**STAINLESS & CARBON STEEL FNPT END ROTOR VALVES, 2 THRU 5-WAY**

VALVE SIZE	A	B	C	D	E	F	G	H	I		
									S-	L-, T-, B-	LL
1/4"	3.88	2.75	.73	.73	1.38	2.75	1.38	1.50	.375	.375	.250
3/8"	3.88	2.75	.73	.73	1.38	2.75	1.38	1.50	.375	.375	.250
1/2"	3.88	2.75	.73	.73	1.38	2.75	1.38	1.50	.500	.375	.250
3/4"	5.06	3.50	.94	.94	1.75	3.50	1.75	1.87	.750	.688	.500
1"	5.31	4.00	1.33	1.33	2.00	4.00	2.00	2.38	1.000	1.000	.750
1 1/4"	5.31	3.50	1.33	1.33	2.25	4.50	2.25	2.38	1.000	1.000	.750
1 1/2"	8.00	4.50	1.56	1.56	3.00	6.00	3.00	2.88	1.500	1.500	1.125
2"	12.00	5.25	1.83	1.83	3.25	6.50	3.25	3.69	2.000	1.875	1.312
2 1/2"	12.00	6.50	2.37	2.37	4.00	8.00	4.00	4.17	2.500	2.500	2.500
3"	18.00	7.75	2.77	2.77	4.88	9.75	4.88	5.82	3.000	3.000	3.000
4"	24.00*	10.00	3.64	3.64	6.09	12.18	6.09	6.84	4.000	4.000	4.000

Dimensions may vary due to design changes. For exact dimensions contact factory.

\*Manual handle lengths do not meet OSHA maximum pull requirements. Other options are available to meet this requirement.

