



TRI-CLAMP END ROTOR VALVES, 2 THRU 5-WAY

VALVE SIZE	A	B	C	D	E	F	G	H	I	
									S-, L-, T-, B-	LL
1/2"	3.88	2.75	.73	.73	1.62	3.25	1.62	1.50	.370	.250
3/4"	5.06	3.50	.94	.94	2.00	4.00	2.00	1.87	.620	.500
1"	5.31	3.50	1.33	1.33	2.16	4.32	2.16	2.38	.870	.750
1 1/2"	8.00	4.50	1.56	1.56	2.78	5.56	2.78	2.88	1.370	1.125
2"	12.00	5.25	1.83	1.83	3.25	6.50	3.25	3.69	1.870	1.312
2 1/2"	12.00	6.50	2.37	2.37	3.88	7.75	3.88	4.17	2.370	2.370
3"	18.00	7.75	2.77	2.77	4.53	9.06	4.53	5.82	2.870	2.870
4"	24.00*	10.00	3.64	3.64	5.65	11.30	5.65	6.84	3.834	3.834
6"	30.00*	13.50	5.25	5.25	7.75	15.50	7.75	8.91	5.782	5.782
8"	36.00*	18.00	6.50	6.50	10.25	20.50	10.25	11.81	7.782	7.782

Dimensions may vary due to design changes. For exact dimensions contact factory.

*Manual handle lengths do not meet OSHA maximum pull requirements. Other options are available to meet this requirement.



Quality Controls, Inc. • 200 Tilton Road • Northfield, NH 03276

Tel: (603) 286-3321 • Fax: (603) 286-7648 • Web: www.qcivalves.com

